

Party Tent Holiday 4M



Clear-span width

400 cm

Side height

230 cm

Ridge height

295 cm

Roof pitch

18°

Bay distance

300/500 cm

Longest component

385/549 cm

Minimum tent length

300/500 cm

Maximum tent length

No limit

Main profile

110 mm x 68 mm x 3 mm

Eave / corner connection

Internal eave insert

Max. allowed wind speed to DIN

80 km/h

Wind Load

0.3 kN/m²

Extension / lean-to options

Extension (max. span 300 cm located anywhere, both sides, any length),
1/2 hexagonal at gable end

Flooring options

Woodenfloor with timber or steel sub-construction
Aluminium cassettefloor with plywood or full aluminiumboards
Compactfloor

Cover



RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2

Special design

Portal beams can be used in place of cross struts

By using woodenfloor with steel sub-construction and weights anchoring can be omitted

By using compactfloor anchoring can be omitted



27.09.2011, www.r-zs.de/en/tents/pdf/21

RÖDER Zelt- und Veranstaltungsservice GmbH
63654 Büdingen Fon: +49 06049 700-0
Verkauf: Am Lautenstein Fax: +49 06049 700-339
Vermietung: An den Ellern Fon: +49 06049 700-309
HRB 3261, Friedberg UST-IdNr.: DE 112607812

Geschäftsführer:
Rüdiger Blasius
Jens Brüggemann
Thomas Roman
St.-Nr.: 020 225 62014

Bank:
WGZ Bank eG
KBC Bank DTLG AG
Fortis Bank
Duns-Nr.: 32-239-9494

IBAN BLZ Konto
DE73 400 600 00 0000 772 633
DE86 500 203 00 0000 295 086
DE15 370 106 00 1102 421 161
info@r-zs.com

SWIFT/BIC
GENO DE MS
BANV DE HB 500
GEBADE 33
www.r-zs.com